

## ◆ 订购码 Ordering Code



IWPTD-1/4



IWPTD-1/8

## ◆ 规格 Specification

<b>Interval time</b>	0.5 to 120 minutes, adjustable	<b>Valve</b>	IWPTD-10, IWPTD-16, IWPTD-22
<b>Discharge time</b>	2 seconds, fixed	<b>Type</b>	2/2-way direct acting
<b>Manual TEST switch</b>	Micro switch	<b>In/Out ports</b>	1/8", 1/4", BSPP or NPT
<b>Supply voltage</b>	24-240V AC/DC 50/60Hz/12 to 380 VAC/DC 50/60Hz	<b>Max. working pressure</b>	0~10Bar, 16Bar, 22Bar
<b>Current consumption</b>	4mA maximum	<b>Orifice</b>	2.0 mm orifice and 1.6mm for 22 bar
<b>Environmental protection</b>	IP65 IP65, NEMA4, IP65-EN60529	<b>Max Media temperature</b>	Max. 90° C
<b>Environment temperature</b>	-40°C—+50°C/ -40° Celcius to 50° Celcius	<b>Defend grade</b>	IP65, NEMA4
<b>Housing material</b>	ABS plastic	<b>Insulation</b>	Thermal group H (200° C)
<b>Connection</b>	DIN43650B	<b>Valve seals</b>	FPM (Viton) seals Forged brass
<b>Indicators light</b>	Red LED	<b>Mounting Positions</b>	Horizontally or Vertically