



DNC-32X50



DNCD-50X100

◆ 订购码 Ordering Code

□	—	DNC	—	63	x	50	—	25	—	S	—	LB
Tube Type: Blank: Square Type T: Tie-Rod Type M: Mickey Mouse Type		Series Code: DNC: ISO6431 Standard Double Action Type DNCD: ISO6431 Standard Two Axis Double Action Type DNCJ: ISO6431 Two Axis Stroke Adjust Type		Cylinder Bore:		Cylinder Stroke:		Adjust Stroke: 25: 25mm 50: 50mm 75: 75mm		Magnet Code: Blank: Without Magnet S: With Magnet		Fixed Type: Blank: Normal Type LB: Front And Back Fixed Type FA: Front Cover Fixed Type(Front Flange Type) FB: Back Cover Fixed Type(Back Flange Type) CA: Back Cover Fixed Type(Single Earring) CB: Back Cover Fixed Type(Double Earring)

◆ 规格 Specification

Bore(mm)	32	40	50	63	80	100	125
Motion Pattern	Double Action						
Working Medium	Filtered Air						
Compression Pressure	1.5MPa						
Max Operating Pressure	1.0MPa						
Min Operating Pressure	0.1MPa						
Buffer	Air Buffer (Standard)						
Condition Temperature	-5~70℃						
Operating Speed	50~800mm/s						
Port Size	G1/2"	G1/4"	G3/8"		G1/2"		

◆ 行程 Stroke

Bore(mm)	Standard Stroke	Buffer Stroke	Stroke Range
32	25 40 50 80 100 125 160 200 250 320 400 500	20	10~2000
40			
50		22	
63			
80		32	
100	35		
125			

◆ DNCB Series Booster Cylinder



DNCB-50X25X50

◆ 规格 Specification

Working Medium	Filtered Air
Compression Pressure	1.5MPa
Max Operating Pressure	1.0MPa
Max Operating Pressure	0.1MPa
Condition Temperature	-5~70℃

◆ 产品介绍 Products Introduction

Booster cylinder combine 2 or ISO15552 standard cylinder with the same bore and stroke, Creat twice or multiple force as standard cylinder. The connection of 2 or more cylinders are linked with the same material compact structure and easy for installation