



SI-40X80



SIJ-40X80-25

## ◆ 订购码 Ordering Code

SI — 63 X 50 — 25 — S — LB

Series Code:  
SI: ISO6431 Standard  
Double Action Type  
SID: ISO6431 Standard  
Two Axis Double Action  
Type  
SIJ: ISO6431 Two Axis  
Stroke Adjust Type

Cylinder Bore:

Cylinder Stroke:

Adjust Stroke:  
25: 25mm  
50: 50mm  
75: 75mm

Magnet Code:  
Blank: Without Magnet  
S: With Magnet

Fixed Type:

Blank: Normal Type  
LB: Front And Back Fixed Type  
FA: Front Cover Fixed Type(Front Flange Type)  
FB: Back Cover Fixed Type(Back Flange Type)  
CA: Back Cover Fixed Type(Single Earring)  
CB: Back Cover Fixed Type(Double Earring)

## ◆ 规格 Specification

Bore(mm)	32	40	50	63	80	100	125	160	200
Motion Pattern	Double Action								
Working Medium	Filtered Air								
Working Pressure	0.1~0.9MPa								
Max Operating Pressure	1.2MPa								
Min Operating Pressure	0.1MPa								
Buffer	Adjustable Buffer								
Condition Temperature	-5~70℃								
Operating Speed	50~800mm/s								
Port Size	G1/8"	G1/4"		G3/8"		G1/2"		G3/4"	

## ◆ 行程 Stroke

Bore(mm)	Standard Stroke	Max. Stroke	Stroke Range
32	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1000	25~1500
40		1200	
50		1500	
63			
80			
100			
125			
160			
200			