



SC-40X80



SU-40X80



SCJ-40X80-25

◆ 订购码 Ordering Code

SC	-	50	X	50	-	25	-	S	-	LB
Series Code:		Cylinder bore:		Stroke:		Adjust Stroke:		Magnet Code:		Fixed Type:
SC: Standard Double Action (Tie-Rod Type) SCD: Double-Shaft Double-Action (Tie-Rod Type) SCJ: Double Axis Double Action Adjustable (Tie-Rod Type) SU: Standard Double Action (Mickey Mouse Type)						25:25mm 50:50mm 75:75mm		Blank: Without Magnet S: With Magnet		Blank: Normal Type LB: Front And Back Fixed Type FA: Front Cover Fixed Type (Front Flange Type) FB: Back Cover Fixed Type (Back Flange Type) CA: Back Cover Fixed Type (Single Earring) CB: Back Cover Fixed Type (Double Earring) SDB: Back Cover Fixed Type TC: Central Trunnion Type

◆ 规格 Specification

Bore (mm)	32	40	50	63	80	100	125	160	200	250	320
Motion Pattern	Double Action										
Working Medium	Air										
Fixed Type	Normal type FA Type FB Type CA Type CB Type SDB Type LB Type TC Type										
Working Pressure Range	0.1~0.9MPa										
Ensured Pressure Resistance	1.35MPa										
Operating Temperature Range	-5~70℃										
Operating Speed Range	50~800mm/s										
Buffer Type	Adjustable Buffer										
Buffer Stroke	24					32				42	33
Port Size	G1/8"	G1/4"	G3/8"			G1/2"		G3/4"		G1"	

◆ 行程 Stroke

Bore(mm)	Standard Stroke	Max Stroke	Permissible Stroke
32	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500	1000	2000
40	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800	1200	2000
50	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1200	2000
63	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000
80	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000
100	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000
125	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000
160	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000
200	25 50 75 80 100 125 160 175 200 250 300 350 400 450 500 600 700 800 900 1000	1500	2000