



MAL 16X25



MALJ 32X25

◆ 订购码 Ordering Code

MAL	-	U	X	20	-	50	-	25	-	S	-	LB
<p>Series Code: MAL: Double Action Type MSAL: Single Extrusion Type MALD: Double-Shaft Double Action Type MALC: Double Shaft Double Action Damping Type MALJ: Double-Shaft And Adjustable Stroke Type</p>		<p>Back Cover Type: Blank: Fishtail Type CM: Rounded Type U: Horizontal Type</p>		<p>Cylinder bore: 16~40mm</p>		<p>Stroke:</p>		<p>Adjust Stroke: 0~100mm</p>		<p>Magnet Code: Blank: Without Magnet S: With Magnet</p>		<p>Fixed Type: Blank: Normal Type LB: Front And Back Fixed Type FA: Front Cover Fixed Type SDB: Back Cover Swinging Type</p>

◆ 规格 Specification

Bore (mm)	16	20	25	32	40
Motion Pattern	Double Action or Single Action				
Working Medium	Air				
Fixed Type	Normal type FA Type SDB Type LB Type				
Working Pressure Range	0.1~0.9MPa				
Ensured Pressure Resistance	1.35MPa				
Operating Temperature Range	-5~70℃				
Operating Speed Range	30~800mm/s				
Buffer Type	Standard Type		Anti-crash cushion		
	Damping Type		Adjustable cushion		
Port Size	MSX0.8		G1/8"		G1/4"

◆ 行程 Stroke

Bore(mm)	Standard Stroke	Max Stroke	Permissible Stroke
16	25,50,75, 80,100 ,125,160,175,200	300	500
20	25,50,75,80,100,125,160,175,200, 250,300	500	650
25	25,50,75,80,100,125,160,175,200,250,300,350,400,450,500	500	650
32	25,50,75,80,100,125,160,175,200,250,300,350,400,450,500	500	650
40	25,50,75,80,100,125,160,175,200,250,300,350,400,450,500	500	650