



◆ 订购码 Ordering Code

4V	2	10	-	06	-	B	-	AC220V	-	W
<p>规格代码:</p> <p>4V: 二(三)位五通电磁阀 4A: 二(三)位五通气控阀 3V: 二位三通电磁阀 3A: 二位三通气控阀</p> <p>Specification Code:</p> <p>4V: Two(Three)-Position Five-Way Solenoid Valve 4A: Two(Three)-Position Five-Way Pneumatic Control Valve 3V: Two-Position Three-Way Solenoid Valve 3A: Two-Position Three-Way Pneumatic Control Valve</p>	<p>系列代码:</p> <p>2: 200 系列</p> <p>Series Code:</p> <p>2: 200 Series</p>	<p>线圈及位数:</p> <p>10: 单头双位置 20: 双头双位置 30C: 双头三位置封闭型 30E: 双头三位置排气型 30P: 双头三位置压力型</p> <p>Coils And Positions:</p> <p>10: Single-Head Double-Position 20: Double-Head Double-Position 30C: Double-Head Three-Position Closed Type 30E: Double-head Three-Position Exhaust Type 30P: Double-head Three-Position Pressure Type</p>		<p>接管口径:</p> <p>06: 1/8" 08: 1/4"</p> <p>Joint Pipe Size:</p> <p>06: 1/8" 08: 1/4"</p>		<p>接管形式及初始状态:</p> <p>空白: 管接式 B: 二位五通板接式 三位五通板接式 NC: 二位三通常闭式 NO: 二位三通常开式</p> <p>Joint Form And Initial State:</p> <p>Blank: Pipe Connection Type B: Two-Position Five-Way Plate Connection type Three-Position Five-Way Plate Connection Type NC: Two-Position Three-Way Normal Close Type NO: Two-Position Three-Way Normal Open Type</p>		<p>标准电压:</p> <p>Standard Voltage:</p> <p>DC12V DC24V AC24V 50Hz/60Hz AC110V 50Hz/60Hz AC220V 50Hz/60Hz AC380V 50Hz/60Hz</p>		<p>接线形式:</p> <p>空白: 标准端子式 LD: 棕色带灯端子式 LD: 白色带灯端子式 W: 引线式</p> <p>Wiring Form:</p> <p>Blank: Standard Connector LD: Brown with Lighting Connector LD: White With Lighting Connector W: Lead Wire type</p>

◆ 规格 Specification

型号/Models	4V210-06	4V220-06	4V230C-06	4V230E-06	4V230P-06	4V210-08	4V220-08	4V230C-08	4V230E-08	4V230P-08
	4A210-06	4A220-06	4A230C-06	4A230E-06	4A230P-06	4A210-08	4A220-08	4A230C-08	4A230E-08	4A230P-08
位通数/Position And Way No	二位五通 Two-Position Five-Way		三位五通 Three-Position Five-Way			二位五通 Two-Position Five-Way		三位五通 Three-Position Five-Way		
有效截面积/Effective Section Area	14mm ² (CV=0.78)		12mm ² (CV=0.67)			16mm ² (CV=0.89)		12mm ² (CV=0.67)		
型号/Model	3V210-06	3V220-06	3A210-06	3A220-06		3V210-08	3V220-08	3A210-08	3A220-08	
位通数/Position And Way No	二位三通/Two-Position Three-Way					二位三通/Two-Position Three-Way				
有效截面积/Effective Section Area	14mm ² (CV=0.78)					16mm ² (CV=0.89)				
接管口径/Joint Pipe Size	进气=排气=排气=G1/8" Air Inlet=Air Outlet=Exhaust=G1/8"					进气=排气=G1/4" 排气=G1/8" Air Inlet=Air Outlet=G1/4" Exhaust=G1/8"				
工作介质/Working Medium	经40微米过滤的空气/40 Micron Filtered Air									
动作方式/Motion Pattern	内部先导式/Inner Guide Type									
使用压力/Working Pressure	0.15~0.8MPa									
最大耐压/Max Pressure Resistance	1.2MPa									
工作温度/Operating Temperature	-5~60℃									
电压范围/Voltage Range	±10%									
耗电量/Power Consumption	AC: 4.5VA DC: 3W									
绝缘保护等级/Insulation & Protection Class	F 级: IP65/ F Class: IP65									
接线形式/Wiring Form	引线式或端子式/Lead Wire Or Connector Type									
最高动作频率/Max Action Frequency	每秒5次/5 Cycle/Second									
最短励磁时间/Shortest Excitation Time	0.05秒/0.05 Second									