



3A410-15



4A410-15



3V410-15



4A410-15



3A420-15



4V420-15



3V420-15



4A420-15

## ◆ 订购码 Ordering Code

**4V**

规格代码:  
4V: 二(三)位五通电磁阀  
4A: 二(三)位五通气控阀  
3V: 二位三通电磁阀  
3A: 二位三通气控阀

Specification Code:  
4V: Two(Three)-Position Five-Way Solenoid Valve  
4A: Two(Three)-Position Five-Way Pneumatic Control Valve  
3V: Two-Position Three-Way Solenoid Valve  
3A: Two-Position Three-Way Pneumatic Control Valve

**4**

系列代码:  
4: 400 系列  
  
Series Code:  
4: 400 Series

**10**

线圈及位数:  
10: 单头双位置  
20: 双头双位置  
30C: 双头三位置封闭型  
30E: 双头三位置排气型  
30P: 双头三位置压力型

Coils And Positions:  
10: Single-Head Double-Position  
20: Double-Head Double-Position  
30C: Double-Head Three-Position Closed Type  
30E: Double-head Three-Position Exhaust Type  
30P: Double-head Three-Position Pressure Type

**06**

接管口径:  
15: 1/2"

Joint Pipe Size:  
15: 1/2"

**B**

接管形式及初始状态:  
空白: 管接式  
B: 二位五通板接式  
三: 三位五通板接式  
NC: 二位三通常闭式  
NO: 二位三通常开式

Joint Form And Initial State:  
Blank: Pipe Connection Type  
B: Two-Position Five-Way Plate Connection type  
Three-Position Five-Way Plate Connection Type  
NC: Two-Position Three-Way Normal Close Type  
NO: Two-Position Three-Way Normal Open Type

**AC220V**

标准电压:  
  
Standard Voltage:  
DC12V  
DC24V  
AC24V 50Hz/60Hz  
AC110V 50Hz/60Hz  
AC220V 50Hz/60Hz  
AC380V 50Hz/60Hz

**W**

接线形式:  
空白: 标准端子式  
LD: 棕色带灯端子式  
LD: 白色带灯端子式  
W: 引线式

Wiring Form:  
Blank: Standard Connector  
LD: Brown with Lighting Connector  
LD: White With Lighting Connector  
W: Lead Wire type

## ◆ 规格 Specification

型号/Models	4V410-15	4V420-15	4V430C-15	4V430E-15	4V430P-15
	4A410-15	4A420-15	4A430C-15	4A430E-15	4A430P-15
位通数/Position And Way No	二位五通 Two-Position Five-Way			三位五通 Three-Position Five-Way	
有效截面积/Effective Section Area	50mm <sup>2</sup> (CV=2.79)			30mm <sup>2</sup> (CV=1.68)	
型号/Model	3V410-15	3V420-15	3A410-15	3A420-15	
位通数/Position And Way No	二位三通/Two-Position Three-Way				
有效截面积/Effective Section Area	50mm <sup>2</sup> (CV=2.79)				
接管口径/Joint Pipe Size	进气=出气=排气=G1/2" Air Inlet=Air Outlet=Exhaust=G1/2"				
工作介质/Working Medium	经40微米过滤的空气/40 Micron Filtered Air				
动作方式/Motion Pattern	内部先导式/Inner Guide Type				
使用压力/Working Pressure	0.15~0.8MPa				
最大耐压力/Max Pressure Resistance	1.2MPa				
工作温度/Operating Temperature	-5~60℃				
电压范围/Voltage Range	±10%				
耗电量/Power Consumption	AC: 4.5VA DC: 3W				
绝缘保护等级/Insulation & Protection Class	F 级: IP65/ F Class: IP65				
接线形式/Wiring Form	引线式或端子式/Lead Wire Or Connector Type				
最高动作频率/Max Action Frequency	每秒5次/5 Cycle/Second				
最短励磁时间/Shortest Excitation Time	0.05秒/0.05 Second				

