



4M210-08



4M220-08

◆ 订购码 Ordering Code

4M

规格代码:
4M: 二位五通板式电磁阀

Specification Code:
4M: Two-Position
Five-Way Namur Mount
Solenoid Valve

2

系列代码:
2: 200 系列
3: 300 系列

Series Code:
2: 200 Series
3: 300 Series

10

线圈及位数:
10: 单头双位置
20: 双头双位置

Coils And Positions:
10: Single-Head Double-
Position
20: Double-Head Double-
Position

06

接管口径:
06: 1/8"
08: 1/4"
10: 3/8"

Joint Pipe Size:
06: 1/8"
08: 1/4"
10: 3/8"

AC220V

标准电压:

Standard Voltage:
DC12V
DC24V
AC24V 50Hz/60Hz
AC110V 50Hz/60Hz
AC220V 50Hz/60Hz
AC380V 50Hz/60Hz

W

接线形式:
空白: 标准端子式
LD: 棕色带灯端子式
W: 引线式

Wiring Form:
Blank: Standard
Connector
LD: Brown with LED
W: Lead Wire type

◆ 规格 Specification

型号/Models	4M210-06	4M220-06	4M210-08	4M220-08	4M310-08	4M320-08	4M310-10	4M320-10
位通数/Position And Way No	二位五通 Two-Position Five-Way							
有效截面积/Effective Section Area	14mm ² (CV=0.78)	16mm ² (CV=0.89)		25mm ² (CV=1.40)		30mm ² (CV=1.68)		
接管口径/Joint Pipe Size	进气=排气=G1/8" Air Inlet=Exhaust=G1/8"	进气=G1/4",排气=G1/8" Air Inlet=G1/4",Exhaust=G1/8"		进气=排气=G1/4" Air Inlet=Exhaust=G1/4"		进气=G3/8",排气=G1/4" Air Inlet=G3/8",Exhaust=G1/4"		
工作介质/Working Medium	经40微米过滤的空气/40 Micron Filtered Air							
动作方式/Motion Pattern	内部先导式/Inner Guide Type							
使用压力/Working Pressure	0.15~0.8MPa							
最大耐压/Max Pressure Resistance	1.2MPa							
工作温度/Operating Temperature	-5~60℃							
电压范围/Voltage Range	±10%							
耗电量/Power Consumption	AC: 4.5VA DC: 3W							
绝缘保护等级/Insulation & Protection Class	F 级: IP65/ F Class: IP65							
接线形式/Wiring Form	引线式或端子式/Lead Wire Or Connector Type							
最高动作频率/Max Action Frequency	每秒5次/5 Cycle/Second							
最短励磁时间/Shortest Excitation Time	0.05秒/0.05 Second							