



BM23531-08



BM23532-08

◆ 订购码 Ordering Code

BM235

规格代码:
BM235: 二位五通,两位三通可
变换板式电磁阀

Specification Code:
BM235: Two-Position
Five-Way and Two-
Position Three-Way
Convertible Namur
Mount Solenoid Valve

3

系列代码:
3: 300系列阀体

Series Code:
3: 300 Series Valve
Body

1

线圈及位数:
1: 单头双位置
2: 双头双位置

Coils And Positions:
1: Single-Head Double-
Position
2: Double-Head Double-
Position

08

接管口径:
08: 1/4"
10: 3/8"

Joint Pipe Size:
08: 1/4"
10: 3/8"

AC220V

标准电压:

Standard Voltage:
DC12V
DC24V
AC24V 50Hz/60Hz
AC110V 50Hz/60Hz
AC220V 50Hz/60Hz
AC380V 50Hz/60Hz

W

接线形式:
空白: 标准端子式
LD: 茶色带灯端子式
W: 引线式

Wiring Form:
Blank: Standard
Connector
LD: Brown with LED
W: Lead Wire type

◆ 规格 Specification

型号/Models	BM23531-08	BM23532-08	BM23531-10	BM23532-10
位通数/Position And Way No	二位五通 或者 两位三通 Two-Position Five-Way or Two-Position Three-Way			
有效截面积/Effective Section Area	25mm ² (CV=1.40)		30mm ² (CV=1.68)	
接管口径/Joint Pipe Size	进气=排气=G1/4" Air Inlet=Exhaust=G1/4"		进气=G3/8", 排气=G1/4" Air Inlet=G3/8", Exhaust=G1/4"	
工作介质/Working Medium	经40微米过滤的空气/40 Micron Filtered Air			
动作方式/Motion Pattern	内部先导式/Inner Guide Type			
使用压力/Working Pressure	0.15~0.8MPa			
最大耐压力/Max Pressure Resistance	1.2MPa			
工作温度/Operating Temperature	-5~60℃			
电压范围/Voltage Range	±10%			
耗电量/Power Consumption	AC: 4.5VA DC: 3W			
绝缘保护等级/Insulation & Protection Class	F 级: IP65/ F Class: IP65			
接线形式/Wiring Form	引线式或端子式/Lead Wire Or Connector Type			
最高动作频率/Max Action Frequency	每秒5次/5 Cycle/Second			
最短励磁时间/Shortest Excitation Time	0.05秒/0.05 Second			