

◆ 订购码 Ordering Code

SMV	-	30	-	1	-	AC220V
Series Code SMV: Miniature Solenoid Valve, 2 Way		Orifice(mm): 16:1.6mm 45:4.5mm 25:2.5mm 50:5.0mm 30:3.0mm 60:6.0mm 35:3.5mm 80:8.0mm 40:4.0mm 100:10.0mm		Port Size: 1: G1/8" 2: G1/4" 3: G3/8" 4:G1/2"		Voltage: DC6V DC12V DC24V DC36V AC24V AC110V AC 220V



◆ 规格 Specification

Model	SMV-16	SMV-25	SMV-30	SMV-35	SMV-40	SMV-45	SMV-50	SMV-60	SMV-80	SMV-100				
Body Material	Brass or stainless steel													
Control Method	Direct Acting/Normal Closed													
Pipe Size	G1/8"	G1/8"	G1/4"	G1/8"	G1/4"	G1/4"	G1/4"	G3/8"	G1/4"	G3/8"	G3/8"	G3/8"	G3/8"	G1/2"
Orifice(mm)	1.6mm	2.5mm	3.0mm	3.5mm	4.0mm	4.5mm	5.0mm	6.0mm	8.0mm	10mm				
Applicable Medium	Air, Water, Steam, Oil, etc													
Pressure Range	0.0~1.6MPa													
Medium Temperature	-10~80℃ (NBR), -10~120℃ (EPDM), -10~150℃ (VITON), -20~200℃ (PTFE)													
Specified Voltage	DC6V, DC12V, DC24V, DC36V, AC24V, AC110V, AC220V, AC120V, AC240V													
Operating Voltage Range	±10%													
Install Method	Horizontal Installation													
Characteristic	Miniature construction at lower consumption, compact design to save space													