

◆ 订购码 Ordering Code

<div style="background-color: #0056b3; color: white; padding: 5px; border-radius: 3px; display: inline-block;">ZL</div>	-	<div style="background-color: #0056b3; color: white; padding: 5px; border-radius: 3px; display: inline-block;">30</div>	-	<div style="background-color: #0056b3; color: white; padding: 5px; border-radius: 3px; display: inline-block;">1</div>	-	<div style="background-color: #0056b3; color: white; padding: 5px; border-radius: 3px; display: inline-block;">AC220V</div>
<p>Series Code ZL: Manifold Solenoid Valve</p>		<p>Orifice(mm): 16:1.6mm 25:2.5mm 30:3.0mm</p>		<p>Port Size: 1: G1/8"</p>		<p>Voltage: DC12V DC24V AC24V AC120V AC240V AC110V AC 220V</p>



◆ 规格 Specification

Model	ZL-16	ZL-25	ZL-30
Body Material	Brass or Stainless steel		
Control Method	Direct acting		
Pipe Size	G1/8"	G1/8"	G1/8"
Orifice (mm)	1.6mm	2.5mm	3.0mm
Applicable Medium	Neutral gas and fluids		
Pressure Range	0.0~1.0MPa		
Medium Temperature	-10~80℃ (NBR seal), -10~120℃ (EPDM seal), -10~150℃ (VITON seal)		
Specified Voltage	DC12V, DC24V, AC24V, AC120V, AC240V, AC110V, AC220V		
Operating Voltage Range	± 10%		
Install Method	Horizontal Installation		
Characteristic	Compact design, threaded port and sub-base connection		