

◆ 订购码 Ordering Code

IWBT

Timer Motorized drain Valve
IWBT: Brass Valve Body
IWNT: Nickel Plated Brass Valve Body
IWST: Stainless Steel Valve Body

1/4

Port Size
 1/4" BSP or NPT
 3/8" BSP or NPT
 1/2" BSP or NPT
 3/4" BSP or NPT
 1" BSP or NPT
 1-1/4" BSP or NPT

M

Manual:
M: Manual Reset /Valve Off
Blank: Without Manual Reset /Valve Off

2

Wire:
2: 2 Wires Without Ground Wire
3: 3 Wires With Ground Wire



IWBT



IWNT



IWST

◆ 规格 Specification

Model	IWBT (Brass)	IWNT(Nickel plated brass)	IWST (Stainless steel)
Operating fluid	Air , Water, Oil		
Ensured pressure resistance	1.6MPa		
Working pressure	0~1..2MPa		
Valve open/Close time	≤7 Seconds		
Rated voltage	AC/DC9~24V, AC110~230V, DC110~250V		
Keeping valve open time	0H:0M:0S-99H59M59S		
Keeping valve closed time	0H:0M:0S-99H59M59S		
Working current	≤7 500MA		
Stall current setting	0-599mA		
Life time	100000 times		
Actuator material	Engineering plastics		
Sealing material	EPDM & PTFE		
Actuator rotation	90°		
Max. torque force	4N.M		
Cable length	0.5m,1.5m Optional		
Environment temperature	-15℃~50℃		
Fluid temperature	2℃~90℃		
Indicator	yes		
Protection class	IP67		