



2V025-08



2V130-15

## ◆ 订购码 Ordering Code

**2V**

Specification Code:  
2V: Two-Position Two-Way Solenoid Valve

**025**

Aperture Of Flow Rate:  
010: 1.0 mm  
025: 2.5mm  
130: 13mm  
250: 25mm

**06**

Port Size:  
M4: M4X0.7  
06: G1/8"  
08: G1/4"  
10: G3/8"  
15: G1/2"  
20: G3/4"  
25: G1"

**AC220V**

Standard Voltage:  
DC12V  
DC24V  
AC24V 50Hz/60Hz  
AC110V 50Hz/60Hz  
AC220V 50Hz/60Hz  
AC380V 50Hz/60Hz

**V**

Oil Seal Code:  
Blank: NBR  
V: VITON (For High Temperature)

## ◆ 规格 Specification

Model	2V010-M4	2V025-06	2V025-08	2V130-10	2V130-15	2V250-20	2V250-25
Working Medium	Air ,Water , Oil						
Motion Pattern	Direct Drive Type			Guide Type			
Type	Normal Close Type						
Aperture of Flow Rate(mm)	1.0	2.5		13		25	
CV Value	0.10	0.23		6.2		23	
Port Size	M4X0.7	G1/8"	G1/4"	G3/8"	G1/2"	G3/4"	G1"
Operation Fluid Viscosity	20 CST (Below)						
Working-pressure	Air , Water ,Oil / 0.05~0.7MPa						
Max. Pressure Resistance	1.2	1.6		1.0			
Operating Temperature Range	-10~+80						
Voltage Range	10%						
Protect Class	IP65						
Power Consumption	AC:4.5VA/DC:3W						
Insulation	F Class						
Material of Body	Aluminum or Brass (Nickel coated)			Brass			
Material of Oil Seal	NBR or VITON			NBR or VITON			
Shortest Excitation Time	0.05 Second						